










Model	CMH M ²	Application	Photo
AirPro-1 Portable Bi-Polar Ioniser	Spaces of up to 50 M ²	Small, Portable and lightweight (1kg) bi-polar ioniser for rooms of up to 50 M ²	
AirPro-2 Battery Powered Bi-Polar Ioniser	Spaces of up to 50 M ²	Rechargeable Battery Powered, lightweight (1.5kg) bi-polar ioniser	
SGFC-400	2300 CMH Approximately 50 M ²	Smaller residential applications, Hotel Rooms, Fan Coils, Heat Pumps, Cassette AirCons	
SG- Matterhorn 880 (1 tube)	1,360 to 5,100 CMH Approximately 112 M ²	Virtually any application	
SG- Matterhorn 882 (2 Tubes)	2,720 to 8,500 CMH Approximately 178 M ²	Virtually any application	
SG- 505E (5-“E” Tubes)	10,200 to 13,600 CMH Approximately 434 M ²	Commercial AHU's	
SG- 505F (5-“F” Tubes)	13,600 to 17,000 CMH Approximately 558 M ²	Commercial AHU's	

Model	CMH M ²	Application	Photo
SG- 508F (8-“F” Tubes)	20,400 to 25,500 CMH Approximately 775 M ²	Commercial AHU's	
AtmosAware Sensor	N/A	The AtmosAware system allows for real time monitoring of CO2, PM2.5, Total Volatile Organic Compounds (TVOC), and also monitors for temperature, humidity, illumination, and noise level.	
Real Time IAQ Monitoring Data	N/A	Building management and continuous IAQ monitoring with a tablet, computer or smartphone	