

PRODUCT FACT SHEET

SGMH-880/882 Series

(With 1 or 2 Ionisation Tubes)



APPLICATION

The SGMH-882 bipolar ionization system is intended to be mounted in the supply duct or air handler of a heating, cooling, or ventilating system. The unit is intended to operate only when air flow is present, thus, power to the ionization unit should be interlocked with fan operation, or controlled via an air pressure switch. The size and number of ionization systems is dependent upon the airflow, size of the space, and severity of the pollution and odors. Ionization can be adjusted with a 5-step knob.

Optional: Air Pressure Switch; Mounting Bracket; Timer; Remote Monitoring Panel

Figure 1

	Tube Size	Tube Number	Flowrate (CFM)	Inches of WG	Pascals Pa	Steady State mA
M-1000	C	(2)	2000	0.0080	2.00	34.00
	D	(2)	3000	0.0241	6.00	35.00
	E	(2)	4000	0.0482	12.00	35.00
	F	(2)	5000	0.0683	17.00	37.00

SPECIFICATIONS

General Product Information

Air Flow Rating	SGMH-880 -5000 CFM; SGMH-882 - 8500 CFM
Pressure Drop	See Figure 1
Housing Material	Flame-Rated, High Impact ABS (Underwriters Laboratories Inc. pending as plenum-rated per UL 1995, 867; file # 313742. Energy Star Certified.)
Weight	6.0 lbs
Max Operation Temp.	200°F (~93°C)

Electrical

Rated Voltage	115 - 250VAC
Frequency	50/60hZ
Power Consumption	6 Watts
Current Draw	37 mA
Internal Fuse	1.0 Amp FST Glass 5mm x 20mm
Field Electrical Connection	Field Electrical Connection; 3-Wire to Jct. Box or Country Specific Cord-Set

Ionization Tube

Material	Mono-Core Composite
Tube Quantity	Model SGMH-880 1 Tube; SGMH-882 2 Tubes
Compatible Tube Sizes	C, D, E, & F
Estimated Tube Life	2 Years or 17,600 Hours

Dimensions

8.75" x 8.5" x 4" See Figure 2 for more details

Approvals

Underwriters Laboratories Inc. pending as plenum-rated per UL 1995, 867; file # 313742. UL 2998; Energy Star Certified.

Figure 2

Duct Cut-Out Dimensions

